

# TILESTIK - DS



## HIGH PERFORMANCE TILE FIXING ADHESIVE

### PRODUCT DESCRIPTION :

TILESTIK-DS is factory blended polymer modified cement based tile adhesive, it is designed for both "new" application of tiles/marble/granite and for "tile on tile" application, Suitable for floors, walls of kitchens and bathrooms, terraces, swimming pools and other areas. Ceramic, glazed tiles and marble can be fixed on existing mosaic, stone, on dry, damp and submerged areas. No messy surface preparation. It has high waterproofing characteristics.

### FEATURES :


- Excellent adhesion.
- Ready to use.
- "NEW" and "tile on tile" application
- Needs only mixing with water.
- Low shrinkage Suitable for thick bed applications (3mm - 12mm).
- Suitable for use in wet areas.
- Sufficient flexible to accommodate normal traffic movement.



### AREA OF APPLICATION :


Fixing Ceramic or glazed tiles in :

- Kitchens.
- Bathrooms.
- Floors.
- Walls.
- Terraces.
- Swimming pools.



### METHOD OF APPLICATION :

- Mix powder to water in the proportion of approx 3 : 1 by volume
- Mix it thoroughly to uniform consistency. After allowing the mixture to stand for 5 to 10 min, stir mixture again just before spreading.
- Apply the mixture on the surface smoothly using the notched trowel maintaining a thickness of 3mm.
- Ensure the total usage of the mix within 25 - 30 min.
- Apply the tiles with a slight twist on the surface within 15 min after the application of Tilestik - DS.
- The theoretical consumption is 60-70 sq. ft per 25kg bag
- PACKING : TILESTIK - DS is available in 10kg and 25kg.



Mfg. & Mrktd. by :

## PROFIX

21, Ballygunge Circular Road, Kolkata - 700 019,  
Unit - 21,3rd Floor, Ph.: 2486 4118, 2486 6454  
Email: [profix@amitbiotech.com](mailto:profix@amitbiotech.com)  
URL: [www.amitbiotech.com/profix](http://www.amitbiotech.com/profix)

